

HTK 105024 L

THREE-WAY TIPPER TRAILER

HUMBAUR
MAKES IT HAPPEN



**TRADE FAIR
DEBUT**

TRADE FAIRDEBUT!

STANDARD EQUIPMENT

Axles made by renowned manufacturers
Maintenance-free parabolic suspension with optimal load balancing
Steel rim tyres at the manufacturer's discretion
2S/2M ABS system (includes ALB function)
ISO 7638 ABS connection
Spindle parking brake
ABS diagnostic connection
Two front ISO 1728 interchangeable coupling heads in red/yellow
Tow bar with 40 mm-diameter DIN screw towing ring, galvanised, can be adjusted using master gauge
Height of the tow bar can be adjusted below the level of the loading area
24-V lighting system with multi-chamber tail lights and LED side marker lights
15-pin connector for lighting
Chassis frame welded and hot-dip galvanised in an immersion bath
Lockable slot for two optional ramps built into the frame
Bridge floor made from 4-mm fine-grained steel
Four pairs of tie-down eyes recessed in the bridge floor
Bridge frame with trough-like supports, hot-dip galvanised
Four rocking ball bearings with two interchangeable rocking bearing pins
450-mm-high laser-welded high-quality steel side plates
Side plates can be folded down at the sides and rear, can be removed and screw swivel-mounted with a central locking system
Rear wall with automatic tailgate unlocking
Side plates have a fully hot-dipped galvanised finish
Rear stanchions galvanised and screwed
Solid galvanised steel front wall can be folded down at the front
Side plate lifting springs on the lateral side plates
Reinforced 12-t gear-supported jack with load and overdrive speed
hydraulic three-sided tilt control, controlled via the towing vehicle (max. 200 bar, up to 90 l/min)
Five-level cylinder with stroke limiter and safety cables
SVK BG3 hydraulic plug-in coupling as a single-circuit connection
Mudguard on the front and rear axle with splash guard system
Two wheel chocks with holder
Side and rear contour marking
Space for single-line registration plate

TECHNICAL DATA

Internal dimension	approx. 5070 x 2420 x 430 mm
Overall dimension	approx. 7010 x 2550 x 1420 mm
Total permissible weight	11,900 kg
Load capacity	approx. 9150 kg
Tyres	235/75 R17.5 inch
Load height	approx. 950 mm

ACCESSORIES* (available as an option)

One pair of aluminium ramps, length approx. 3570 mm x width approx. 400 mm, Load capacity 8000 kg each with wheelbase approx. 2000 mm, Weight 55 kg/piece, with arrestor, carrier rollers and folding supports

Plastic tool boxes approx. 750 x 360 x 350 mm (LxWxD) including bracket mounted under the loading area, lockable

Plug holders with two parking sockets

Additional accessories available on request



Important safety information! The trailer may only be used with express adherence to all road traffic, professional association and load securing regulations. We assume no responsibility for printing or other errors or omissions. Subject to technical modifications. Illustrations are similar, can include accessories available at an extra charge. Some trailers show special equipment. Net prices in Euro plus applicable VAT and shipping costs, as well as registration certificate. Products are subject to ongoing technical changes. All dimensions are approximate values and refer to the standard vehicle without accessories. Printed in Germany. Reprint prohibited. As at: 03/19.