

FOR THE BEST TRAVEL COMFORT



KTA

3000 / 3500



HUMBAUR
TRAILERS UP TO 3,5to



Subject to change without notice. All dimensions are approximate values and refer to the standard vehicle without accessories. Illustrations may include special accessories.

humbaur.com



► **Standard equipment: KTA**

- Warp-resistant chassis with a solid hot-dip galvanised loading frame
- Suitable for cable reels with a diameter of up to 2800 mm and a width of 1450 mm
- Easy operation of the loading frame with or without cable reel
- Zero-play loading frame mounting using dowel pins — ensuring safe handling
- No barriers to negotiate when fitting the cable reel
- Ball bearings on the cable drum attachment
- Solid jockey wheel and rear support
- Stable telescopic crank support



CABLE REEL TRAILER

► Cable reel trailer KTA							
Model	Permissible gross weight	Load capacity in kg	Overall dimension (L x W x H) mm	Internal dimensions (L x W x H) mm	braked	Load height in mm	Tyres in inches
KTA 3000	3000	2240	4725 x 2370 x 2090	2200 x 1450 x 2850	✓	900	14
KTA 3500	3500	2700	4725 x 2370 x 2090	2200 x 1450 x 2850	✓	900	14

Subject to change without notice. All dimensions are approximate values and refer to the standard vehicle without accessories. Illustrations may include special accessories. We assume no responsibility for printing or other errors or omissions. Date: 03/18