

FlexBox DRY

- > 30 mm sandwich panels
- Insulated roof fitted as standard
- Double-hinged rear doors
- Rear portal & auxiliary frame hot-dip galvanised
- LED interior lighting with motion detector
- Sliding tie-down points on the floor
- Step with handgrip at the rear
- Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

TUNDED MAILE P TUNDED MAILE P TUNDED MAILE P TUNDED MAILE TO TUNDES OF TO TUNDED

The FLEXBOX superstructures are checked by TÜV NORD according to Code XL.



FlexBox COOL

- ▶ 60 mm sandwich panels
- ▶ 65 mm insulated floor
- Double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- LED interior lighting with motion detector
- Step with handgrip at the rear
- Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King

FlexBox FREEZE

- ▶ 80 mm front wall & roof
- ▶ 65 mm side wall panels
- ▶ 120 mm insulated floor
- ▶ 85 mm double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ► LED interior lighting with motion detector
- Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King



The FLEXBOX superstructures are certified in accordance with ATP and HACCP regulations.





PERFECT FOR THE FIAT DUCATO



Additional accessories and individual design solutions on request!



FLEXBOX DRY	W/B 3000 mm (L1)	3450 mm (L2)	3800 mm (L3)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	2435 x 2035 x 2085	2935 x 2035 x 2085	3435 x 2035 x 2085	3685 x 2035 x 2085	3935 x 2035 x 2085
Steel construction weight in kg	525	595	665	700	735
GRP structure weight in kg	290	330	370	390	410
FLEXBOX COOL	W/B 3250 mm	3450 mm (L2)	3800 mm (L3)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	2370 x 2070 x 2065	2870 x 2070 x 2065	3370 x 2070 x 2065	3620 x 2070 x 2065	3870 x 2070 x 2065
Steel construction weight in kg	670	760	850	895	940
GRP structure weight in kg	445	505	565	595	625
FLEXBOX FREEZE	W/B 3250 mm	3450 mm (L2)	3800 mm (L3)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	2320 x 2050 x 1970	2820 x 2050 x 1970	3320 x 2050 x 1970	3570 x 2050 x 1970	3820 x 2050 x 1970
Steel construction weight in kg	750	850	950	1000	1050
GRP structure weight in kg	495	565	635	670	705

Important safety information: The vehicle may only be used with express adherence to all road traffic, professional association and load securing regulations. We assume no responsibility for printing or other errors or omissions. Subject to change without notice. All dimensions are approximate values and refer to the standard vehicle without accessories. Printed in Germany. Reprint prohibited · Illustrations similar, some trailers show special equipment · ATP, Code XL and HACCP certifications only in specific designs · As at: 08/18.